



Россия

8 800 775 29 79
www.spe-pm.ru
info@sp-eng.ru

Офис в Москве
ул. Сретенский б-р, д. 6/1 стр. 1

Офис в Самаре
ул. Красный Пахарь. д. 21

Узбекистан

+ 998 99 066 99 44
f.matchanov@sp-eng.ru

Офис в Ташкенте
Мирабадский р-н,
ул. Афросиеб, д. 14

Беларусь

+375 44 567 000 8
i.strelskij@digitalmade.by

Центр этикетирования
и маркировке в Минске
ул. Краснозвездная,
д. 18Б, оф. 57

Аппликаторы Worldpack: описание и технические характеристики

Applicator Specifications		Stepper Applicator with Keypad	Stepper Applicator with PLC	Servo Applicator with PLC	Servo Applicator with motorised Rewinder	Dual Reel Servo Applicator with PLC	Dual Servo Applicator with PLC	Dual Servo Applicator with motorised Rewinder
Label	Label Material	Paper/PP	Paper/PP	Paper/PP	Paper/PP	Paper/PP	Paper/PP	Paper/PP
	Max. Label Roll Diameter	270mm	270mm	270mm	300mm. Can be customised upto 400mm	300mm. Can be customised upto 400mm	300mm. Can be customised upto 400mm	300mm. Can be customised upto 400mm
	Label Roll Core Diameter	76mm	76mm	76mm	76mm	76mm	76mm	76mm
	Suitable Label Height	150mm	150mm	150mm	100mm	100mm	100mm	100mm
	Label length	Min. 16mm Max. 300mm	Min. 16mm Max. 300mm	Min. 16mm Max. 300mm	Min. 16mm Max. 300mm	Min. 16mm Max. 300mm	Min. 16mm Max. 300mm	Min. 16mm Max. 300mm
	Back Paper Rewinder Diameter	150mm	150mm	150mm	200mm	190mm	200mm	200mm
Label Application	Label Dispensing Speed	25m/min.	30m/min.	35m/min.	50m/min.	50m/min.	50m/min. and 100m/min with double gripper	50m/min. and 100m/min with double gripper
	Labeling Accuracy	+/-1mm	+/-1mm	+/-1mm	+/-0.5mm	+/-0.5mm	+/-0.5mm	+/-0.5mm
Control	Operating Systems	Microcontroller	PLC	PLC	PLC	PLC	PLC	PLC
	Control Panel	Keypad	Operating Desk with HMI	Operating Desk with HMI	Operating Desk with HMI	Operating Desk with HMI	Operating Desk with HMI	Operating Desk with HMI
Alarm	Paper Break	✓	✓	✓	✓	✓	✓	✓
	Reel End	Optional	Optional	Optional	Yes	Yes	Yes	Yes
	Drive Fault	-	✓	✓	✓	✓	✓	✓
Sensor	Label Sensor	NPN, 24V	NPN, 24V	NPN, 24V	NPN, 24V	NPN, 24V	NPN, 24V	NPN, 24V
	Product Sensor	NPN, PNP, 24V	NPN, PNP, 24V	NPN, PNP, 24V	NPN, PNP, 24V	NPN, PNP, 24V	NPN, PNP, 24V	NPN, PNP, 24V
Facility to Synchronised with line speed through encoder		✓	✓	✓	✓	✓	✓	✓
Label Positions	Top, side and bottom	✓	✓	✓	✓	✓	✓	✓
Dimensions		900mm x 650mm x 400mm	900mm x 650mm x 400mm	900mm x 650mm x 400mm	900mm x 500mm x 400mm	970mm x 1020mm x 270mm	900mm x 1500mm x 400mm	900mm x 1200mm x 400mm
Weight		20-25 Kg	20-25 Kg	20-25 Kg	25-30 Kg	35-40 Kg	40-50 Kg	50-55 Kg
Environment	Operating Temperature	5 - 40°C	5 - 40°C	5 - 40°C	5 - 40°C	5 - 40°C	5 - 40°C	5 - 40°C
	Humidity	30 - 85%, non-condensing	30 - 85%, non-condensing	30 - 85%, non-condensing	30 - 85%, non-condensing	30 - 85%, non-condensing	30 - 85%, non-condensing	30 - 85%, non-condensing

